



- Balance of Quality and Cost
- Wide Selection of Wattages
- Vertical or Horizontal Orientation



**NVC**®  
**Downlights**

# NDLJ Horizontal Series



NDLJ35\*



NDLJ37\*

### Description

Ceiling recessed compact fluorescent downlights in horizontal orientation. **IP20 (NDLJ35\* Series)** and **IP40 (NDLJ37\* Series)** as options.

### Construction

- Bezel - Robust steel bezel
- Reflector - High purity aluminum reflector in matt finish
- Safety glass - Toughened glass (NDLJ37\* Series)
- Ceiling clips - Stainless steel

### Specification

- For compact fluorescent lamps (not included)

### Applications


- Offices and corridors
- Retails areas
- Reception and circulation areas
- Hotels and restaurants
- Universities, schools and colleges

model	Dia.	H	Cut-Out
NDLJ354/374	Ø 147	90	Ø 133
NDLJ355/375	Ø 178	100	Ø 154
NDLJ356/376	Ø 190	100	Ø 168
NDLJ358/378	Ø 234	100	Ø 210


Dimensions in mm

### Photometric Data

NDLJ355/1-E  
Lamp: NVC CFL 1x14W



NDLJ355/2-E  
Lamp: NVC CFL 2x14W



### Options

- High purity aluminum reflector in polished specular finish



### Color



Model		Lamp Rated						Quantity/CTN	CTN Dimension
		FHS	FDE	FTE	FAS	FMS	FHE		
NDLJ354/1-E	NDLJ374/1-E	Max.23W	Max.8W	Max.11W	Max.23W	Max.23W	Max.18W	12pcs	380x320x325mm
NDLJ355/1-E	NDLJ375/1-E	Max.23W	Max.12W	Max.14W	Max.23W	Max.23W	Max.18W	12pcs	430x350x410mm
NDLJ355/2-E	—	Max.12W	Max.12W	Max.14W	—	—	—	12pcs	430x350x410mm
NDLJ356/1-E	NDLJ376/1-E	Max.23W	Max.12W	Max.18W	Max.23W	Max.23W	Max.18W	12pcs	430x350x410mm
NDLJ356/2-E	NDLJ376/2-E	Max.12W	Max.12W	Max.18W	Max.14W	Max.15W	Max.18W	12pcs	430x350x410mm
NDLJ358/2-E	NDLJ378/2-E	Max.12W	Max.12W	Max.24W	Max.14W	Max.15W	Max.18W	6pcs	410x270x510mm

# NDLJ Vertical Series



NDLJ31\*



NDLJ36\*




model	Dia.	H	Cut-Out
NDLJ3125/3625	Ø 98	110	Ø 85
NDLJ3135/3635	Ø 124	125	Ø 105
NDLJ314/364	Ø 147	155	Ø 125
NDLJ315/365	Ø 178	197	Ø 155
NDLJ316/366	Ø 190	202	Ø 165


Dimensions in mm

### Photometric Data

NDLJ3125-ACB  
Lamp: NVC CFL 1x13W



NDLJ3135-ACB  
Lamp: NVC CFL 1x13W



### Description

Ceiling recessed compact fluorescent downlights in vertical orientation. **IP20 (NDLJ31\* Series)** and **IP40 (NDLJ36\* Series)** as options.

### Construction

- Bezel - Robust steel bezel
- Reflector - High purity aluminum reflector in diamond&streak finish
- Safety glass - Toughened glass(NDLJ36\* Series)
- Ceiling clips - Spring steel

### Specification

- For compact fluorescent lamps(not included)

### Applications

- Offices and corridors
- Retails areas
- Reception and circulation areas
- Hotels and restaurants
- Universities, schools and colleges

### Options

- High purity aluminum reflector in matt finish



### Color



Model		Lamp Rated						Quantity/CTN	CTN Dimension
		FHS	FDE	FTE	FAS	FMS	FHE		
NDLJ3125	NDLJ3625	Max.12W	Max.5W	Max.8W	—	Max.15W	—	40pcs	570x240x520mm
NDLJ3135	NDLJ3635	Max.18W	Max.8W	Max.14W	Max.23W	Max.20W	Max.15W	40pcs	670x280x580mm
NDLJ314	NDLJ364	Max.23W	Max.8W	Max.14W	Max.23W	Max.23W	Max.18W	12pcs	485x330x340mm
NDLJ315	NDLJ365	Max.23W	Max.12W	Max.24W	Max.23W	Max.23W	Max.18W	12pcs	575x390x450mm
NDLJ316	NDLJ366	Max.23W	Max.12W	Max.24W	Max.23W	Max.23W	Max.18W	12pcs	605x410x450mm


# NVC Energy-saving Lamps



- Average life 10,000 hours with stable performance, no flicker
- High potential savings in energy, procurement and maintenance costs
- 80% CO<sub>2</sub> reduction comparing to traditional lamps
- Heat resistant PBT housing, no yellowing
- Best match for NVC downlights



### Mini-Star FHS Series




	a	b	h
FHS05	Ø40	Ø42	79
FHS08	Ø40	Ø46	83
FHS12	Ø40	Ø46	90
FHS15	Ø52	Ø60	98
FHS18	Ø52	Ø60	107
FHS23	Ø52	Ø60	118

Dimensions in mm



### T3/T4 2U FDE Series




	a	h
FDE03(T3)	Ø35	100
FDE05(T3)	Ø35	105
FDE08(T3)	Ø35	130
FDE12(T4)	Ø42	151

Dimensions in mm



### T3/T4 3U FTE Series



	a	h
FTE08(T3)	Ø42	109
FTE11(T3)	Ø42	119
FTE14(T3)	Ø42	134
FTE18(T4)	Ø48	160
FTE24(T4)	Ø48	169

Dimensions in mm



### T3 Half-Spiral FAS Series



	a	b	h
FAS14	Ø46	Ø50	120
FAS18	Ø46	Ø60	120
FAS23	Ø46	Ø60	135

Dimensions in mm



### T2 Mini-Spiral FMS Series



	a	b	h
FMS09	Ø40	Ø48	90
FMS13	Ø40	Ø48	105
FMS15	Ø40	Ø48	109
FMS20	Ø49	Ø60	110
FMS23	Ø49	Ø60	120

Dimensions in mm



### T3 Full-Spiral FHE Series



	a	h
FHE13	Ø48	110
FHE15	Ø48	115
FHE18	Ø48	125

Dimensions in mm



## NVC LIGHTING TECHNOLOGY CORPORATION

Add: NVC Industrial Park, Ruhu, Huizhou, Guangdong, P. R. China 516021

Tel: +86-752-2786890 2786891 2786887

Fax: +86-752-2786892 2786689

E-mail: [oversea01@nvc-lighting.com](mailto:oversea01@nvc-lighting.com) [oversea20@nvc-lighting.com](mailto:oversea20@nvc-lighting.com)

Http: [www.nvc-lighting.com](http://www.nvc-lighting.com)